## Optimization

**MINTELLIGENT** 

## "Go Green" with Intelligent Compressed Air® Products!

It's a worldwide problem. Compressed air leaks and inefficient blowoffs can waste thousands of dollars of electricity per year, affecting your company's production costs and bottom line. For many plants, the leakage alone accounts for up to 30% of the total compressed air cost.

EXAIR can help your company "go green" with six easy to follow steps. It's as simple as finding the leaks, making the repairs, controlling the air use, and upgrading to efficient blowoffs. EXAIR's Intelligent Compressed Air<sup>®</sup> products can help you accomplish these steps so your compressed air system becomes more efficient, along with the benefit of drastically lowering your energy costs.

SCAN & WATCH the video!

https://exair.co/04-optv



#### Six Steps To Optimizing Your Compressed Air System

## Measure the air consumption to find sources that use a lot of compressed air.

EXAIR's **Digital Flowmeter™** accurately measures compressed air usage and monitor waste. Trends can be monitored to find excessive air use. Detect leaks at compressed air fittings when the machinery is off. Regular monitoring can detect leaks that develop as the machinery ages. Pressure Sensing and Hot Tap models are also available.

- Easy to install No adjustments or calibrations needed.
- Digital readout displays actual airflow through pipe
   Pages 10-16



EXAIR's **Ultrasonic Leak Detector** can help you identify costly leaks in your compressed air system. Leaks can account for 30% of total compressor output! In many cases, finding small leaks can quickly pay for the leak detector.

- Detects leaks up to 20' (6.1m) away
- Accurate in noisy industrial environments



## Upgrade your blowoff, cooling and drying operations using engineered compressed air products.

EXAIR's **Super Air Knives<sup>™</sup>**, **Super Air Amplifiers<sup>™</sup>**, and **Super Air Nozzles<sup>™</sup>** dramatically reduce air consumption and noise. EXAIR's **Digital Sound Level Meter<sup>™</sup>** can identify and isolate the source of the noisy blowoffs.

Low cost-replaces noisy blowers

Improves blowoff performance and safety

Pages 17, 20, 46, 55



COMPRESSED AIR

#### Turn off the compressed air when it isn't in use.

EXAIR's **EFC**<sup>™</sup> is an electronic flow control that minimizes compressed air use by turning off the compressed air when no part is present. For use on blowoff, drying, cooling, conveying and static elimination operations.

- Easy hook up; 100-240 VAC with eight function timer
  Photoelectric sensor withstands water and dust
- Page 7

Page 18

## 5. Use intermediate storage of compressed air near the point of use.

An EXAIR 60 gallon **Receiver Tank** can be installed at the point of high demand so there is an additional supply of compressed air available for a short duration. Meets ASME pressure vessel code.

Eliminates fluctuations in pressure and volume
Vertical, space saving design

Page 240

## 6. Control the air pressure at the point of use to minimize air consumption.

EXAIR **Pressure Regulators** permit easy selection of an operating pressure that will allow the air product to work properly without using excessive amounts of compressed air. Reducing the air pressure from 100 PSIG to 80 PSIG reduces energy use by almost 20%.

- Modular design
- Many sizes available
- Pressure gauge included

Page 235







6





**Electronic Flow Control minimizes** compressed air use for blowoff, drying, cooling, conveying and static elimination operations!

### Dramatically reduces compressed air costs by turning off the air when no part is present!



#### What Is The EFC?

EXAIR's EFC is a user-friendly electronic flow control for compressed air that is designed to minimize compressed air use on blowoff, drying, cooling, conveying and static elimination operations. The EFC combines a photoelectric sensor with a timing control that limits compressed air use by turning it off when no part is present. The timing control permits easy tuning to the application requirements while providing flexibility in sensing distance. The EFC also has eight programmable on and off modes.

#### Why The EFC?

For most companies, the air compressor uses more electricity than any other type of equipment. One simple operation that uses compressed air can easily waste thousands of electricity dollars per year if not properly controlled. The EFC has been designed to improve efficiency by minimizing compressed air use and, as a result, reduce compressed air costs. It turns on the air only when a part is present and provides just enough air to complete a specific task or operation.

The EFC has an easy electrical connection for voltages from 100 to 240VAC, 50/60Hz making it suitable for applications throughout the world. The compact photoelectric sensor has a sensitivity adjustment and detects objects up to

3' (1m) away. The sensor has superior immunity to noise and inductive loads that are common to industrial environments and installs easily in tight spaces with the supplied mounting bracket. The control system provides flexibility with numerous valve operating modes and timing delays. The polycarbonate enclosure is suitable for use in a wide range of applications including those located in wet environments.

INTELIGEN

COMPRESSED AI

#### **Applications**

- · Auto body blowoff
- Package cleaning
- Part drying after wash
- Dust removal
- Scrap removal
- **Filling operations**
- Cooling hot parts
- Neutralizing static
- Cleaning molded parts

#### Advantages

- Easy electrical hook-up; 100-240VAC, 50/60Hz
- NEMA 4/IP66 environments
- Compact sensor for mounting in tight spaces
- Eight function analog timer for on/off, pulsing and delay control
- Timer setting from 0.10 sec. to 120 hrs.
- Sensor withstands water and dust for accurate readings
- Sensor has superior immunity to noise and inductive loads Sensor has long distance sensing up to 3 feet (1m)

#### **Electronic Flow Control**

	Model # Description		
	9055	EFC Electronic Flow Control, 40 SCFM (1,133 SLPM), solenoid valve, 1/4 NPT	
ſ	9056	EFC Electronic Flow Control, 100 SCFM (2,832 SLPM), solenoid valve, 1/2 NPT	
	9057	EFC Electronic Flow Control, 200 SCFM (5,664 SLPM), solenoid valve, 3/4 NPT	
ſ	9064	EFC Electronic Flow Control, 350 SCFM (9,911 SLPM), solenoid valve, 1 NPT	
Ì	Models controlling two solenoid valves are available. Contact EXAIR for details.		





Photoelectric sensor withstands water and dust.





#### \$2,045.22 Annual Air Savings On A Flat Panel Display Blowoff

A flat panel display manufacturer runs 3 shifts. It takes a 40 second cycle to produce one fully assembled display. Prior to packaging, they use EXAIR's 12" (305mm) Super Ion Air Knife at 40 PSIG (2.8 BAR) to blow across the display to remove any static electricity, dust, debris and plastic flash from the panel surface. The air ran constantly. The displays are under the airflow only 10 seconds. Thirty seconds pass until the next display is in position. They manufacture 675 displays per shift (7.5 hrs.) for a total of 2,025 displays manufactured per day.



The timer was set to the "interval" setting when detecting the flat panel displays. The sensor was mounted 1" (25mm) prior to the Super Ion Air Knife blowoff station. When it detected the flat panel, it turned the air on immediately and started the 10 second timing sequence for closing the valve (shutting the air off). In the event the conveyor stopped, the air would no longer cycle on again until the next flat panel was detected.

8 = 24/7

The timing control unit and the photoelectric sensor are equipped with a 9' (2.74m) power cord. The timing control unit is housed in a polycarbonate NEMA 4 / IP66 water tight enclosure.

There are four models of the EFC. Each includes the timing control unit and photoelectric sensor with a choice of solenoid valve sizes of 40, 100, 200 and 350 SCFM (1,133, 2,832, 5,664 and 9,911 SLPM).

EFC Specifications			
Power Supply Input	100-240VAC, 50/60Hz, 0.25 - 0.45A		
Power Supply Output (To Sensor)	24VDC at 0.65A		
Sensor	12-24VDC input, consumes 30mA		
Sensing Range	Diffuse reflective to 3' (1 meter)		
Enclosure Rating	NEMA 4 / IP66		
Temperature Rating	-13°F to 131°F (-25°C to 55°C)		
RoHS Compliant	Yes		
CE Compliant	Yes		
Mandala senstra llin n tura selan sidus luga sens rusilabla. Canta et EVAID fan dataila			

Models controlling two solenoid valves are available. Contact EXAIR for details.

#### **Old Method**

EXAIR's 12" (305mm) Super Ion Air Knife was supplied at 40 PSIG to clean the displays.

At 40 PSIG, EXAIR's 12" (305mm) Super Ion Air Knife consumes 20.4 SCFM (577 SLPM)

Non-stop blowing of 1,440 minutes (24 hours) per day x 20.4 SCFM = 29,376 SCF (831,341 SL) air usage per day.

#### **EFC Solution**

The EFC was installed to shut off the compressed air for 30 seconds of the 40 second cycle. (Turns air off for 75% of the cycle.)

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

#### Before the EFC installation:

29,376 SCF/1,000 = 29.38 x \$0.25 = \$7.34 air cost per day.

#### With the EFC installed:

The EFC shut the air off during the three 30 minute shift changes. Upon sensing the display, the timer turned on the compressed air for only 10 seconds of each 40 second cycle (25% of the time).

1,440 minutes per day – 90 minutes between shifts =

- 1,350 minutes of operation per day.
- 1,350 minutes x 25% = 337.5 minutes of air per day

337.5 minutes x 20.4 SCFM = 6,885 SCF (194,846 SL) air usage per day. 6,885 SCF/1,000 = 6.89 x \$0.25 = \$1.72 air cost per day

\$7.34 (old air cost) - \$1.72 (new air cost) =

\$5.62 savings per day x 7 days a week = \$39.33 savings per week x 52 weeks a year = \$2,045.22 savings per year.



#### \$5,012.28 Annual Air Savings For Pre-Paint Bumper Cleaning

A manufacturer of car bumpers installed a 60" (1524mm) Super Ion Air Knife in the down draft cleaning area prior to their paint booth. The bumpers enter that area in the same orientation as they would when mounted to the automobile, moving at 10' (3m) per minute with a 12" (305mm) space between bumpers. The bumpers are under the blow off for 10 seconds. 6 seconds pass with no bumper in the ionized airflow. The operation runs around the clock with three shifts.



The timer was set to "interval" and the sensor mounted next to the Super Ion Air Knives. When it detected a bumper, it immediately turned on the air for 10 seconds. If the conveyor stopped, it would not turn the air on again until it detected the next bumper.

#### \$3,393 Annual Air Savings On A Tank Blowoff Operation

A company that refurbishes large tanks runs the tanks through an oven on a conveyor line to burn off old paint. Only one tank at a time can be processed and each takes 6 minutes to complete the journey. Super Air Knives are used for blowoff at the exit of the oven.

However, the tank travels through the oven for 5 minutes before it reaches the knives for blowoff. At 80 PSIG (5.5 BAR), the four knives consume 348 SCFM (9,854 SLPM). Once the tanks have been blown off, the conveyor stops, the air is shut off, and a new tank is loaded at the other end. The operation runs 30 tanks per day, 5 days a week.



The timer was set to "on/off delay". The sensor was mounted at the oven exit (1 minute away from the blowoff station). When the sensor detected a tank, the timer turned the air on for one minute, just as the next tank reached the blowoff station.

#### Old Method

EXAIR's 60" (1524mm) Super Ion Air Knife was supplied at 40 PSIG to clean the bumper.

At 40 PSIG, EXAIR's 60" (1524mm) Super Ion Air Knife consumes 102 SCFM (2,887 SLPM).

Non-stop blowing of 1,440 minutes (24 hours) per day x 102 SCFM = 146,880 SCF (4,156,704 SL) air usage per day.

#### **EFC Solution**

The EFC was installed to shut off the compressed air for the 6 seconds where no bumper was present - an on cycle reduction of 37.5%. 1,440 minutes x 37.5% = 540 minutes of off time per day

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

#### Before the EFC installation:

146,880 SCF/1,000 = 146.88 x \$0.25 = \$36.72 air cost per day.

With EFC installed: 146,880 SCF x 62.5% on cycle = 91,800 SCF/1,000 = 91.8 x \$0.25 = \$22.95 air cost per day. \$36.72 (old air cost) - \$22.95 (new air cost) =

\$13.77 savings per day x 7 days per week = \$96.39 savings per week x 52 weeks per year = \$5,012.28 savings per year.

#### **Old Method**

It takes 6 minutes to complete the process.

6 minutes x 348 SCFM=

2,088 SCF (59,090 SL) 2,088 SCF x 30 tanks = 62,640 SCF (1,772,712 SL)

#### **EFC Solution**

The EFC was installed to shut off the compressed air for the 5 minutes where no tank was present (one minute of air on).

1 minute x 348 SCFM = 348 SCF x 30 tanks = 10,440 SCF (295,452 SL)

#### **Cost Difference**

Most large plants know their air cost. If the actual cost is unknown, \$0.25 per 1,000 SCF (28,329 SL) is reasonable.

**Before the EFC installation:** 62,640 SCF/1,000 = 62.64 x \$0.25 = \$15.66 air cost per day.

With the EFC installed: 10,440 SCF/1,000 = 10.44 x \$0.25 = \$2.61 air cost per day. \$15.66 (old air cost) - \$2.61 (new air cost) =

\$13.05 savings per day x 5 days per week = \$65.25 savings per week x 52 weeks per year = \$3,393 savings per year.





#### **Digital Flowmeter**

## **Digital Flowmeter™**

## Monitor compressed air usage and waste!

PRESSEDA

#### What is the Digital Flowmeter?

Anyone serious about lowering their energy consumption, operating an efficient plant or optimizing their compressed air system knows that measuring compressed air consumption is the first step toward efficiency. EXAIR's Digital Flowmeter is the easy way to monitor compressed air consumption and waste! The digital display shows the exact amount of compressed air being used, making it easy to identify costly leaks or inefficient air products. Many companies install the Digital Flowmeter on each major leg of their air distribution system to constantly monitor and benchmark compressed air usage.

#### Why the Digital Flowmeter?

The Digital Flowmeter has an LED display that directly indicates the SCFM or m<sup>3</sup>/hr volume of airflow through that pipe. Models from 1/2" to 4" iron pipe are in stock. Each Digital Flowmeter is calibrated for the pipe size to which it is mounted. The Digital Flowmeter is designed for permanent or temporary mounting to the pipe. It requires the user to drill two small holes through the pipe using the included drill bit and locating fixture. The two flow sensing probes of the flowmeter are inserted in these holes. The unit seals to the pipe once the clamps are tightened. No cutting, welding, adjustments or calibration are ever required. If the unit needs to be removed, block-off rings are available. NEMA Type 4 (IP66) meters available. Consult the factory for NEMA 4 meters.

#### **How it Works?**

These flowmeters measure flow by maintaining a temperature differential between the two probes inserted into the compressed air pipe. One probe is kept warmer than the other and mass flow rate is determined by the amount of heat required to maintain the temperature differential. The flow rate, in SCFM or m<sup>3</sup>/hr, is shown on the large four-digit display. A 4-20 mA output and pulse output permit remote display of the flow value and data collection.

#### Advantages

All EXAIR Digital Flowmeters are available in three fundamental versions and offer these advantages over traditional flowmeters.

- No moving parts
- Summing Remote Display and Data Logger available
- Optional RS-485 output serial communication board available
- Sensitive at low flows
- No calibration or set up required
- Includes all components for installation
- Models from 1/2" to 4" Schedule 40
   iron pipe in stock

CONTROL ENGINEERING

**N** 

2020

ENGINEERS' CHOICE AWARDS

FINALISTS

PRODUC

YEAR

CONTROL ENGINEERING

**i R** 

**I** 

2021

ENGINEERS CHOICE AWARDS

FINALISTS

-70

- Models are available for sizes 1/2" to 8" in iron pipe
- Models are available for sizes 3/4" to 4" in copper pipe
- Models are available for sizes 25mm through 101mm in aluminum pipe
- · Easy to install



For Technical Assistance, Call an EXAIR Application Engineer 1-800-903-9247 Toll Free FAX (866) 329-3924 • E-mail: techelp@exair.com • www.exair.com





CE



#### **Flowmeter Versions**

2021

ENGINEERS' CHOICE AWARDS

FINALISTS

ENGINEERING

2020

ENGINEERS' CHOICE AWARDS

FINALISTS

EXAIR.com

These three versions of digital flowmeter can be used on Schedule 40 iron pipe, Type L copper pipe, or the nominal pipe sizes listed on Page 13.

**Standard** The original Digital Flowmeter provides accuracy and an easy to read display of current compressed air consumption, daily consumption or cumulative consumption. Digital Flowmeter with optional Data Logger shown at left.

**Pressure Sensing** Digital Flowmeters monitor pressure and flow. A pressure sensor is mounted between the two flow sensing probes. The pressure signal is provided as a second milliamp output. The display can be configured to show pressure or flow. The pressure signal is also available through wired or wireless serial outputs. The pulse output is replaced with a transistor output configured as a lowpressure alarm when the pressure drops below 50 PSIG. Available on 2" and 50mm or larger flowmeters.

**Hot Tap** This meter allows for installation under pressure, eliminating the need to isolate and remove pressure from the pipe it is being installed upon. It incorporates two valves that the probes pass through and a muffler that collects chips from the drilling process. It takes an equally short amount of installation time as the standard meters. Available on 2" and 50mm or larger flowmeters.

"Caution" labe Warns not to remove pressurized. Apply v Power Plug

**Order Direct** 

Ship From Sta

## **Digital Flowmeter Accessories**

#### **Need an EXAIR Drill Guide?**

Basic kits for EXAIR's Digital Flowmeters include all of the components for installation, which are: a drill guide to locate the holes for the sensing probes accurately, a drill bit so the holes are the proper size and a hex wrench for installing the pipe clamp securely. If you have purchased a Digital Flowmeter in the past and have these components for the same sized flowmeter, you can order the flowmeter without a drill guide kit by adding the "-DG" suffix to the model number. (Model Number Configurator on Page 13). Drill guides can also be ordered separately.



EXAIR's Drill Guide for Digital Flowmeter.

#### What is the Summing Remote Display?

EXAIR's Summing Remote Display for the Digital Flowmeter has a four-digit LED display that makes it easy to monitor compressed air consumption from a convenient location. With the push of a button, the display cycles to show the current air consumption, usage for the previous 24 hours, and total cumulative usage. The Summing Remote Display shows that flow measurement, the daily and cumulative usage and is frequently used when the Digital Flowmeter is in an obscure, hard to read location. Regular monitoring of the air usage of a machine, process or department makes it possible to save thousands of dollars per year in compressed air waste by identifying the costly leaks or inefficient air products. The Summing Remote Display is CE and RoHS compliant

#### What is the USB Data Logger?

EXAIR's award-winning Model 9147 USB Data Logger connects directly to your Digital Flowmeter and is simple to use. Download the software to configure the Data Logger to record your flow rate from once a second (about nine hours of data) up to once every 12 hours (over 2 years!).

When the Data Logger is removed from the Digital Flowmeter and plugged into a computer, the data can be viewed in the software or exported directly into Microsoft Excel<sup>®</sup>. The Data Logger is available pre-installed on the Digital Flowmeter. Data Loggers can be added to your Digital Flowmeter by adding a suffix to the model number (Model Number Configurator on Page 13). They can also be ordered separately.

#### **Drill Guides**

Model #	Description
900817	Drill Guide Kit Only, 1/2", 3/4", 1", 1-1/4", 1-1/2" Schedule 40 and Type L Copper (double ring mount)
901281	Drill Guide Kit Only, 2" and 2.5" Schedule 40 and Type L Copper (single ring mount)
900939	Drill Guide Kit Only, 3" Schedule 40 and Type L Copper
900871	Drill Guide Kit Only, 4" Schedule 40 and Type L Copper
900872	Drill Guide Kit Only, 5" Schedule 40 and Type L Copper
901151	Drill Guide Kit Only, 6" Schedule 40 and Type L Copper
902098	Drill Guide Kit Only, 8" Schedule 40 and Type L Copper
901994	Drill Guide Kit Only for 2" and Up Aluminum Compressed Air Pipe

#### **Summing Remote Display**

Model #	Description		
9150	LED Readout displays SCFM		
9150-M3	9150-M3 LED Readout displays m <sup>3</sup> /hr		
It is pre-wired Mounting har	with 50' (15.2m) of cable and is powered by the Digital Flowmeter dware is included.		



EXAIR's Summing Remote Display for the Digital Flowmeter.

## USB Data Logger



EXAIR's USB Data Logger for the Digital Flowmeter.

#### What are Block-Off Rings?

Block-Off rings are used to safely cover and seal any holes which were drilled for the Digital Flowmeters. They allow for moving a Digital Flowmeter to multiple locations in your piping system.

#### **Block-Off Rings**

Model #	Description	
901327	Block-Off Rings for 9090	
901328	Block-Off Rings for 9091	
901329 Block-Off Rings for 9092 or 9092-M3		
901331	Block-Off Rings for 9094 or 9094-M3	

Model #	Description
901332	Block-Off Rings for 9095 or 9095-M3
901333	Block-Off Rings for 9096 or 9096-M3
901334	Block-Off Rings for 9097 or 9097-M3
901335	Block-Off Rings for 9098 or 9098-M3
902099	Block-Off Rings for 90100

12



#### **Digital Flowmeter Model Numbering**

1. Choose the **Version** of Digital Flowmeter using one of these prefixes:

#### Version

Standard	No Prefix
Hot Tap DFM (available on 2" and 50mm or larger)	Н
Pressure Sensing DFM (available on 2" and 50mm or larger)	Р

#### 2. Choose the **Size** of your compressed air pipe:

#### Size

Model #	Pipe Size
9090	1/2"
9091	3/4"
9092	1"
9093	1-1/4"
9094	1-1/2"
9095	2"
9096	2-1/2"
9097	3"
9098	4"
9099	5"
90100	6"
90101	8"
91025	for nominal pipe 25mm
91040	for nominal pipe 40mm
91050 for nominal pipe 50mm	
91063	for nominal pipe 63mm
91076 for nominal pipe 76mm	
91101	for nominal pipe 101mm

#### 3. Choose the **Configuration** you want by picking one suffix below:

#### Configuration

Model #	Configuration	
-DG	removes Drill Guide	
-DAT includes Data Logger w/ Drill Guide		
-DG-DAT includes Data Logger, removes Drill Guide		
CU	for Copper Pipe w/ Drill Guide	
CU-DG for Copper Pipe, removes Drill Guide		
CU-DAT	CU-DAT for Copper Pipe includes Data Logger w/ Drill Guide	
CU-DG-DAT	CU-DG-DAT for Copper Pipe includes Data Logger, removes Drill Guide	

-M3	Metric (displays m³/hr) w/ Drill Guide		
-M3-DG	Metric (displays m³/hr), removes Drill Guide		
-M3-DAT	DAT Metric (displays m³/hr) includes Data Logger w/ Drill Guide		
-M3-DG- DAT	Metric (displays m³/hr) includes Data Logger, removes Drill Guide		

#### **Configuration Samples**

Version	Size	Configuration	Summary
	9090	-DG	Model 9090-DG Standard 1/2" DFM without a Drill Guide
Н	9098	CU	Model H9098CU Hot Tap 4" DFM for Copper Pipe w/Drill Guide
Р	9095		Model P9095 Pressure Sensing 2" DFM w/Drill Guide
	91025	-DAT	Model 91025-DAT 25mm Nominal Pipe DFM w/Drill Guide and Data Logger



11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 • E-mail: techelp@exair.com • www.exair.com



13

**rder Direct** e Ship From Si

EXAIR's Digital Flowmeter is a product designed to monitor compressed air consumption and flow, offering an easy solution for tracking these metrics. Equipped with a digital display, it provides the precise amount of compressed air being used. This feature allows for the identification of costly leaks or inefficient air products. The device is easy to install, sensitive at low flows, requires no calibration or setup, and includes all components necessary for installation.

#### **Digital Flowmeter**

(Add specific Configuration from Page 13)

Model #	Pipe Size	Flow Range*	
9090	1/2"	1–100 SCFM (1.7-170 m <sup>3</sup> /hr)	
9091	3/4"	1–150 SCFM (1.7-255 m <sup>3</sup> /hr)	
9092	1"	2–200 SCFM (3.4-340 m <sup>3</sup> /hr)	
9093	1-1/4"	4-400 SCFM (6.8-680 m <sup>3</sup> /hr)	
9094	1-1/2"	4-400 SCFM (6.8-680 m <sup>3</sup> /hr)	
9095	2"	6–600 SCFM (10.2-1020 m <sup>3</sup> /hr)	
9096	2-1/2"	8-800 SCFM (13.6-1359 m <sup>3</sup> /hr)	
9097	3"	12-1200 SCFM (19.8-2040 m <sup>3</sup> /hr)	
9098	4"	20-2000 SCFM (34.2-3398 m <sup>3</sup> /hr)	
9099	5"	30-3000 SCFM (51-5100 m <sup>3</sup> /hr)	
90100	6"	50-5000 SCFM (85.2-8496 m <sup>3</sup> /hr)	
90101	8"	100-6000 SCFM (169.8-10194 m <sup>3</sup> /hr)	

#### **Digital Flowmeter Type L Copper Pipe**

Add specific Configuration from Page 13)				
Model #	Pipe Size	Flow Range*		
9091CU	3/4"	1–150 SCFM (1.7-255 m <sup>3</sup> /hr)		
9092CU	1"	2–200 SCFM (3.4-340 m <sup>3</sup> /hr)		
9093CU	1-1/4"	2–200 SCFM (3.4-340 m <sup>3</sup> /hr)		
9094CU	1-1/2"	4-400 SCFM (6.8-680 m <sup>3</sup> /hr)		
9095CU	2"	6–600 SCFM (10.2-1020 m <sup>3</sup> /hr)		
9096CU	2-1/2"	8-800 SCFM (13.6-1359 m <sup>3</sup> /hr)		
9097CU	3"	10-1000 SCFM (17-1699 m <sup>3</sup> /hr)		
9098CU	4"	20-2000 SCFM (34-3398 m <sup>3</sup> /hr)		

Calibrated range. Usable range higher. Please consult factory.

Note: Flow ranges for all Digital Flowmeters in top 3 tables except for Hot Tap Digital Flowmeters, shown below.

#### **Digital Flowmeter -Nominal Pipe Size - Millimeters**

(Add specific Configuration from Page 13)			
Model #	Pipe Size	Flow Range*	
91025	25mm	2-200 SCFM (3.4-340 m <sup>3</sup> /hr)	
91040	40mm	4-400 SCFM (6.8-680 m <sup>3</sup> /hr)	
91050	50mm	6-600 SCFM (10.2-1020 m <sup>3</sup> /hr)	
91063	63mm	8-800 SCFM (13.6-1359 m <sup>3</sup> /hr)	
91076	76mm	10-1000 SCFM (17-1699 m <sup>3</sup> /hr)	
91101	101mm	20-2000 SCFM (34-3398 m <sup>3</sup> /hr)	



**EXAIR's Digital Flowmeter family is** available in many sizes from stock.

#### Hot Tap Digital Flowmeter -**Schedule 40 Iron Pipe**

#### (Add specific Configuration from Page 13)

Model #	Pipe Size	Flow Range*
H9095	2"	6-600 SCFM (10.2-1020 m <sup>3</sup> /hr)
H9096	2-1/2"	8-800 SCFM (13.6-1359 m <sup>3</sup> /hr)
H9097	3"	12-1200 SCFM (20-2039 m <sup>3</sup> /hr)
H9098	4"	20-2000 SCFM (34-3398 m <sup>3</sup> /hr)
H90100	6"	50-5000 SCFM (85-8495 m <sup>3</sup> /hr)
H90101	8"	100-6000 SCFM (169-10194 m <sup>3</sup> /hr)

#### Hot Tap Digital Flowmeter -**Type L Copper Pipe**

#### (Add specific Configuration from Page 13)

, ad specific configuration nonn age 15,			
Model #	Pipe Size	Flow Range*	
H9095CU	2"	6-600 SCFM (10.2-1020 m <sup>3</sup> /hr)	
H9096CU	2-1/2"	8-800 SCFM (13.6-1359 m <sup>3</sup> /hr)	
H9097CU	3"	10-1000 SCFM (17-1699 m <sup>3</sup> /hr)	
H9098CU	4"	20-2000 SCFM (34-3398 m <sup>3</sup> /hr)	
H90100CU	6"	40-4000 SCFM (68-6796 m <sup>3</sup> /hr)	

Digital Flowmeter Specifications				
	Wired	Hot Tap	Pressure Sensing	
Accuracy	5% of reading plus 1% of range for flows from 10% to 100% of indicated range at air temperatures between 20°F and 120°F.	5% of reading plus 1% of range for flows from 10% to 100% of indicated range at air temperatures between 20°F and 120°F.	PRESSURE: +/- 2 PSIG maximum. +/- 0.5 PSIG at 68°F.	
Operating Pressure	200 PSIG maximum on Sch. 40 iron and on Type L Copper below 3". Consult EXAIR for other materials and higher pressures	130 PSIG maximum on Sch. 40 iron. Consult EXAIR for other materials and higher pressures	200 PSIG maximum on Sch. 40 iron and on Type L Copper below 3". Consult EXAIR for other materials and higher pressures	
Input Power	250 mA at 24V DC	250 mA at 24V DC	250 mA at 24V DC	
Output resistance	600 Ohms maximum	600 Ohms maximum	600 Ohms maximum	
Wetted Materials	Stainless Steel, Gold, Thermal epoxy, Viton	Stainless Steel, Gold, Thermal epoxy, Viton, PTFE, Aluminum	Stainless Steel, Gold, Thermal epoxy, Viton	
<b>Ring Material</b>	Aluminum	Aluminum	Aluminum	
Display	Four digit LED	Four digit LED	Four digit LED	
<b>Response Time</b>	One second to 63% of change in value at flows above 30% of range	One second to 63% of change in value at flows above 30% of range	One second to 63% of change in value at flows above 30% of range	
Pressure Range	N/A	N/A	0-145 PSIG operating range 200 PSIG maximum 145 PSIG full sc ale of mA output For best accuracy, avoid pressures above 145 PSIG	
Compliance	CE and RoHS	CE and RoHS	CE and RoHS	

Note: For use with compressed air and nitrogen only.

14



#### Small Digital Flowmeter – Schedule 40 Iron Pipe\*\*

	Pipe	ŀ	٩
Series	Size	in	mm
9090	1/2"	3.31	84
9091	3/4"	3.49	89
9092	1"	3.87	98
9093	1-1/4"	4.24	108
9094	1-1/2"	4.62	117







#### Large Digital Flowmeter – Schedule 40 Iron Pipe\*\*

	Pipe	А	
Series	Size	in	mm
9095	2"	5.34	136
9096	2-1/2"	6.09	155
9097	3"	6.71	171
9098	4"	7.71	196
9099	5"	8.84	224
90100	6"	9.84	250
90101	8"	11.84	301







#### Small Digital Flowmeter – Type L Copper Pipe\*\*

	Pipe	ŀ	A
Series	Size	in	mm
9091CU	3/4"	3.49	89
9092CU	1"	3.68	93
9093CU	1-1/4"	3.87	98
9094CU	1-1/2"	4.24	108





ID sized

for Pipe Material

#### Large Digital Flowmeter – Type L Copper Pipe\*\*

	Pipe	ŀ	A
Series	Size	in	mm
9095CU	2"	5.09	129
9096CU	2-1/2"	5.84	148
9097CU	3"	6.34	161
9098CU	4"	7.34	186

Large Digital Flowmeter -

in

5.1

5.6

6.3

7.3

129

142

161

186

**Nominal Pipe\*\*** 

Series

91050

91063

91076

91101

Pipe Size

50mm

63mm

76mm

101mm



3.34"	-		-
85mm		0	
2.36" 60mm			
		0	



3.34" 85mm

2.36" 60mm

#### Small Digital Flowmeter – Nominal Pipe\*\*

	Pipe	ŀ	A
Series	Size	in	mm
91025	25mm	3.49	89
91040	40mm	4.24	108



Power

1.71<sup>'</sup>

►O





\*\* If dimensions are critical for mounting, please consult the factory

11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 • E-mail: techelp@exair.com • www.exair.com



drawings at EXAIR.com

0





## 

#### Hot Tap Digital Flowmeter – Schedule 40 Iron Pipe

	Pipe	А	
Series	Size	in	mm
H9095	2"	6.43	163
H9096	2-1/2"	7.20	183
H9097	3"	7.82	199
H9098	4"	8.82	224
H90100	6"	10.95	278
H90101	8"	12.95	329



# 3.14"

EXAIR.con

#### Hot Tap Digital Flowmeter – Type L Copper Pipe

	Pipe	A		
Series	Size	in	mm	
H9095CU	2"	6.18	157	
H9096CU	2-1/2"	6.95	177	
H9097CU	3"	7.45	189	
H9098CU	4"	8.45	215	
H90100CU	6"	10.45	265	





Todel: 901552

The Hot Tap Digital Flowmeters allow installation when compressed air piping is under pressure. By eliminating the need to isolate and remove pressure from the pipe, these compressed air flowmeters

reduce installation time while maintaining safety.



16









## Digital Sound Level Meter™

## **Prevent worker-related hearing loss!**

#### What Is The Digital Sound Level Meter?

EXAIR's Model 9104 Digital Sound Level Meter is an easy to use instrument that can measure and monitor the sound level pressure in a wide variety of industrial environments. The source of loud noises can be quickly identified and isolated so corrective measures can be taken to reduce or eliminate the problem.



For compressed air noise, it is often as simple as replacing the existing inefficient blowoffs with EXAIR's engineered compressed air products such as the Super Air Knife, Super Air Amplifier or Super Air Nozzles. In many cases, the EXAIR products can reduce noise levels by 10 dBA which is perceived as cutting the sound volume in half.

#### Why The Digital Sound Level Meter?

Hearing loss induced by high noise in the workplace is a common problem. Exposure to high noise levels for an extended period of time can lead to permanent hearing loss for workers not wearing proper hearing protection. The Digital Sound Level Meter can help employers protect workers by monitoring noise levels so they don't exceed the limits shown in OSHA Standard 29 CFR - 1910.95(a). Failure to comply can result in hefty fines.

OSHA Maximum Allowable Noise Exposure									
Hours per day (constant noise)	8	7	4	3	2	1	0.5		
Sound level dBA	90	91	95	97	100	105	110		

OSHA Standard 29 CFR - 1910.95 (a)

Accurate and responsive, the Digital Sound Level Meter measures the decibels of the sound and displays the reading on the large LCD display that has a backlight button for easier viewing. An "F/S" response time button provides a choice of slow response measurements for comparatively stable noise measurement or fast for varying noise. The "Max Hold" setting will measure the maximum noise level of sounds and updates continuously if a louder sound is detected. Certification of accuracy and calibration traceable to NIST (National Institute of Standards and Technology) is included.

#### Advantages

- Measures sound level range from 35 dB 130 dB (Low: 35 to 100; High: 65 to 130 dB)
- Frequency range 31.5Hz 8kHz
- A and C weightings (check compliance with safety regulations and acoustic analysis)
- Slow (1 sec) and fast (125ms) response settings to check peak and average noise levels
- Maximum hold feature to measure peak sound levels
- Accuracy is  $\pm$  1.5 dB
- NIST Certification included



- Four digit LCD display in 0.1 dB steps with backlight
- Battery life is 50 hours (typical) with low battery alert
- Automatic power off after 15 minutes of non-use
- Meets CE, ANSI and IEC Type 2 SLM standards
- Tripod mounting ideal for taking long term measurements (tripod not included)
- Removable windscreen for use in windy conditions to reduce misreads
- Includes protective carrying case, 9V battery, instruction manual and removable windscreen







The Sound Level Meter identifies a potential source of hearing loss.



Model 9104 Digital Sound Level Meter comes complete with removable wind screen, battery and a protective case.

#### **Ultrasonic Leak Detector**

## **Ultrasonic Leak Detector**

# Locate costly leaks in your compressed air system!

#### What Is The Ultrasonic Leak Detector?

The Ultrasonic Leak Detector (ULD) is a hand-held, high quality instrument that can locate costly leaks in a compressed air system.



**m INTELLIGENT** 

A person using the ULD need only aim it in the direction of a suspected leak. When a leak is present, an audible tone can be heard with the use of the headphones, and the LED display will light. Testing the various unions, pipes, valves and fittings of a complete installation can be done quickly and effectively at distances up to 20' (6.1m) away!

#### Why The Ultrasonic Leak Detector?

Plants that aren't maintained can easily waste **up to 30%** of the compressor output through leaks that go undetected. Compressing air is an expensive operation. Saving the wasted compressed air reduces overall operating costs. In large plants, the cost of a small air leak may be insignificant, but many small leaks when located and repaired can amount to huge energy savings.



Ultrasonic sound is a range of sound that is above human hearing capacity. Most people can hear frequencies from 20 Hz to 20 kHz. Sound from 20 kHz to 100 kHz cannot be heard and is called "ultrasonic". The Model 9207 Ultrasonic Leak Detector converts ultrasonic sound emissions to a range that is audible to people. (The sound generated by the ULD is 32 times lower in frequency than the sound that is received.)

#### **Advantages**

- Detects any pressurized air leak up to 20 feet (6.1m) away
- Converts ultrasound to an audible frequency
- LED display confirms the leak location
- · Detects leaks in noisy industrial environments
- Sensitivity controls provide accurate detection
- Not affected by contaminants or windy conditions
- Includes accessories to detect leaks in hard to reach areas
- Rugged carrying case
- Complies with the International Electrotechnical Commission (IEC) 61325-1

#### **Applications**

- Locates leaks in air, steam and non-flammable gas systems including pipes, fittings, valves, cylinders and pressure vessels
- Finds the source of bearing and gear wear
- Locates arcing in an electrical system
- Detects refrigeration and air conditioning system leaks
- Locates leaks in brake systems, tubes, tires and radiators
- · Senses cracks in moving rubber v-belts
- Detects leaks in vacuum systems
- Checks condition of engine seals



CE

LED indicators on the Ultrasonic Leak Detector show the exact source of the leak or problem.







## **Ultrasonic Leak Detector**

In a plant where loud noise levels exist, it is very difficult to locate leaks by merely listening for them. Most plant noises are in the normal audible range of human hearing, while air escaping from a small orifice is ultrasonic. The ULD can be adjusted to filter out background noise using a "+" or "-" sensitivity adjustment. The parabola or tubular extension (shown below) can also be attached to the ULD to mask out intense background noise. The ULD detects only the ultrasonic sounds that are generated.



Ultrasonic sound is directional in transmission and is loudest at the source. Turbulence created by the air forced through a small orifice generates ultrasonic sound. This emitted sound is called "white noise" and occurs when the air moves from a high pressure area such as a pipe or vessel and escapes to a low pressure area such as the room. The Ultrasonic Leak Detector converts the turbulent flow to a frequency that can be heard using the earbuds. As the ULD moves closer to the leak, more LEDs on the display light to confirm the source of the leak.

In some cases, the suspected leak is in a hot area and/or close to moving parts. The tubular extension and parabola make it possible to probe these difficult locations from a distance to isolate the leak.



The Model 9207 Ultrasonic Leak Detector comes complete with a hard-shell plastic case, earbuds, parabola, tubular adaptor, tubular extension and 4 AA batteries.



11510 Goldcoast Drive • Cincinnati, OH 45249-1621 • Phone (513) 671-3322 FAX (513) 671-3363 • E-mail: techelp@exair.com • www.exair.com



The Model 9207 Ultrasonic Leak Detector with tubular extension quickly pinpoints a costly leak in a noisy industrial environment.

#### Find Leaks -

#### **Pay For Your Ultrasonic Leak Detector**

Consider one small leak that is equivalent to a 1/16" (1.6mm) diameter hole. At 80 PSIG (5.5 BAR), it consumes 3.8 SCFM or 108 SLPM.

Most large plants know their air cost.

If you don't know your actual cost per 1,000 SCF, a reasonable average is \$0.25 per 1,000 SCF (28,329 SL).

Dollars consumed per hour = SCFM consumed x 60 minutes x cost/1,000 SCF

- = 3.8 × 60 × \$0.25/1,000
- = \$0.06 per hour
- = \$1.44 per 24 hour period
- = \$10.08 per week
- = \$524.16 per year



